



BCR-3008/1.32DV

Article-No.: 72889

Digital Video Recorder (8 Channels), MPEG4, 1.32TB, 200fps, DVD-RW, 230VAC

Mainfeatures

8 Loop-through Video Inputs / VGA, Comp. Outputs
Pentaplex Operation
Recording Speed: 200 ips. max.
1.32Tbyte SATA HDD (no HDD extention possible)
Secondary Storage / Archiving via USB and DVD-RW
RS-232/RS-485 Ports (PC and Telemetry Control)

Alarm Inputs / Outputs
MPEG-4 Video Compression
Video Resolution 704x576 Pixels max.
Recording Modes: Time, Motion, Alarm and Emergency
Multiple Language On-screen Menu Control
Ethernet Connectivity (Remote Viewer Program incl)


Specifications

Series	eneo BC Series
Operation mode	Pentaplex
Operation Mode	live, playback, record, backup, network
Video standard	PAL/NTSC (automatic selection)
Video inputs (amount)	8
Video inputs	1Vp-p, (C)VBS, 75ohms, BNC (loop-through)
IP channels	-
Main video outputs	VGA, composite (CVBS)
Video outputs	1Vp-p (C)VBS, 75ohms, BNC
Spot monitor	composite (CVBS)
Audio inputs	-
Alarm inputs	8x TTL, programmable as NC/NO
Motion detector	22x18 (396) grid, Sensitivity levels: 5
Covert camera mode	available
Alarm triggers	contact, video loss, motion detection, acoutic
Alarm outputs	Relay contact (NO/NC)

Specifications (continued)

Alarm notification	e-Mail, remote software
Max. recording resolution	704x576
Compression standard	MPEG-4 ASP
Compression standard	advanced compression engine provides smaller data size without significant picture quality distortion. 4 steps selectable
Max. recording rate	200 B./Sek.
Max. recording rate	@ 352 x 288
Recording speed	200 ips at 352x288 Px., 100 ips at 704x288 Px., 50 ips at 704x576 Px. (PAL)
Digital storage media	SATA HDD, Built-in DVD-RW
Harddisk capacity (internal)	1,32 TB
Max. harddisk capacity (internal)	2 TB
Pre-alarm recording	no
Post-alarm recording	available
Playback	full screen, 4 channel split, 6 channel split, 8 channel split, PiP, split sequence
Zoom function	2x
Search function	date/time, event, calendar, bookmark
Integrated writer	DVD
Secondary Storage	USB 2.0 interface. Network Data Export: AVI, JPG, BMP
Control units (external)	remote control, mouse
Remote access	remote software, browser
Menu languages	German, English, French, Italian, Polish, Spanish, Russian
Network	10/100 Base-Tx, RJ45
Network protocols	TCP/IP, DHCP, DDNS
Transmission rate (Network)	50 ips (D1), 200 ips (CIF), PAL
Firmware update	USB Flash drive
Interfaces external storage	USB
Serial interfaces	RS-232C, RS-485
Serial interfaces	(PTZ control)
Password protection	administrator, manager and users
Supply voltage	12VDC
Power consumption	80W
Temperature range (operation)	+5°C ~ +40°C
Housing	Steel metal with plastic front, desktop design
Colour	black
Dimensions (HxWxD)	88x436x345mm
Weight	6kg
Parts supplied	19" rack mount angle, manual, IR remote controller, PSU, remote viewer software, mouse
Special features	Indication of remaining memory capacity (in hours). Displayed in the setup menu
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	KBD-BVR-100	System Keyboard with 3-Axis Joystick for BCR Series DVR's, 12VDC

Your partner for eneo products:

