

ZELARIS_IP VC

Article-No.: 76003

Client Version for Zelaris_IP Server
for one Workstation

Mainfeatures

Server/Video Client incl. WebServer w. JAVA Client
Live Display, Recording, Playback, Alarm Processing
MJPEG Recording Format (external Back-up possible)
Zoom Function at Live and Playback
PC Platform Win2000 or XP

Integrated Matrix with 64 ind. Inputs / 25 Outputs
Different Update Rates from 1 to 25ips
Integrated Motion Detector / Channel programmable
Up to 80 Different Pre-configured Multi Screens
Different Passwort Levels



Specifications

Software Categorie	Video Management
Series	eneo Zelaris_IP
Operation system	Windows 2003, Windows XP, Windows Vista, Windows 2008, Windows 7
On-screen display	VGA card for display all live pictures
Demo version	time limit
Hardware recommendation (CPU)	Core2Duo
Hardware recommendation (HD capacity)	120 GB
Hardware recommendation (RAM)	1024 MB
Hardware requirement (CPU)	P4 2.8GHz
Hardware requirement (HD capacity)	60 GB
Hardware requirement (RAM)	1024 MB
Licensing type	per client
Licensing method	Dongle
Languages (client)	German, English, French, Italian, Spanish, Portuguese, Czech, Polish
Support of mobile units	no
Alarm management	eMail, OPC-Server, OPC-Client, scripting language, FTP

Specifications (continued)

Alarm management	yes
Control units (external)	System Keyboard, Mouse, Jog Shuttle, Keyboard
Decoder support	no
Site maps	yes
Multi monitor operation	yes
PTZ Support	yes
Recording settings	choosable per channel
Recording functions	time triggered, permanent, motion detector, contact, OPC
Supported network suppliers	Arecont, Avermedia, Aviosys, Axis, Basler, Bosch, Canon, CBC, Convision, Dallmeier, Dedicated Micros, D-Link, Eltis, Emitall, eneo, Flexwatch, Geutebrück, Grandtec, Hawking, Hunt, Inform, Intellinet, IQEye, JVC, Kingwave, Levelone, Levo, Levono, Lindy, Lumenera, Mobi, Mobotix, NKF Siqua, Orite, Panasonic, Pelco, Pixford, Security Center, Sensormatic, Siemens, Sony, Stardot, Sweex, Toshiba, TRenDnet, Trust, VC, VCenter, Vidisys, Vivotek, VLC, Xannet, Y-Cam
Supported video sources	network camera, digital video recorder, network encoder, analogue camera
Support of video grabbers	no
Managable video sources max.	64
Analysis mode	live, archive
Activity detection	yes
Card skimming	no
Face identification	no
Number plate recognition	no
Left luggage recognition	no
Object classification	no
Object tracking	no
People loitering	no
People counter	no
Smoke/fire detection	no
Direction detection	no
Obstruction detection	yes
Product training	available
Analysis Functions	Activity detection, Obstruction detection

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	S-PRO V.2	Multi-button Jog & Shuttle Multimedia Controller
	WS ZELARIS_IP	Training Management Software Zelaris_IP
	ZELARIS_DECODER	MPEG-4/H.264 Decoder Licence for Zelaris Client, per Workstation

Your partner for eneo products:

