



VK-133/PH

Article-No.: 91773

1/3" Board Camera, B/W,
3.7mm Pinhole Lens, 380TVL,
12VDC

Mainfeatures

CCD B&W Board Camera
Resolution of 420 Horizontal Lines
Internal Synchronization
F3.5/3.7mm Pinhole Lens Element

1/3" CCD Sensor
Electronic Shutter Control (ESC)
High Sensitivity
Supply Voltage: 12VDC



Specifications

System	black&white
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Active picture elements	290,000 (H) 500 x (V) 582
Synchronization	internal
Gamma correction	0.45
Horizontal resolution	420 TVL
Sensitivity (at 50% video signal)	0.5Lux at F1.2 (Videor measurement result), 5.6Lux at F4.0
Low speed shutter	no
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no
Aperture Correction (APC)	yes
IR cut filter	no
Video outputs	composite (VBS)
Lens type	fixed focal length
Lens	F4.0/3.7mm (pinhole type)

Specifications (continued)

Focal length	3,7 mm
Horizontal angle of view	65°
Iris control	no
MOD (Minimum object distance)	0,1 m
Illumination	no
Serial interfaces	no
Temperature range (operation)	-10°C ~ +50°C
Hidden cable management	no
Protection rating	-
Supply voltage	12VDC
Power consumption	1.2W
Dimensions (HxWxD)	32x32x14mm
Weight	30 g
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
	VT-PS12DC-9	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. open Ends

Your partner for eneo products:

