



VK-1319

Article-No.: 91866

1/3" Cylinder Camera, B&W,
3.6mm, 420TVL, 12VDC

Mainfeatures

CCD b&w cylinder camera with integrated lens
Resolution of 420 horizontal lines
H & V aperture (APC)
High sensitivity of 0.65Lux (F2.0)
Weatherproof aluminium housing

1/3" Super HAD CCD
Automatic shutter control (ESC)
Internal synchronization
Supply voltage: 12VDC
Mounting stand with swivel head


Specifications

System	black&white
Video standard	CCIR
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Active picture elements	290,000, 500(H) x 582(V)
Synchronization	internal
Gamma correction	0.45
Horizontal resolution	420 TVL
Sensitivity (at 50% video signal)	0,23 Lux
Sensitivity (at 50% video signal)	at F1.2 (measured)
Automatic electronic shutter (ESC)	yes
Low speed shutter	no
Automatic gain control (AGC)	yes
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no

Specifications (continued)

IR cut filter	no
Video outputs	composite (VBS)
Lens type	fixed focal length
Lens	F2.0/3.6mm w/o. iris
Focal length	3,6 mm
e-PTZ support	no
Digital zoom	no
Horizontal angle of view	69°
Iris control	no
MOD (Minimum object distance)	0,1 m
Illumination	no
Activity detection	no
Serial interfaces	no
Cable connection	Wiring for video and voltage supply made, accessible from outside (approx. 0.5m long, Video: BNC jack 12/24V input: for DC plug 2.1/5.5mm)
Temperature range (operation)	-10°C ~ +50°C
Housing material	aluminium
Housing	outdoor
Integrated wall mount	no
Hidden cable management	no
Sunshield	no
Window heater	no
Colour (housing)	black
Vandalism resistant	no
Protection rating	IP67
Alarm inputs	-
Alarm outputs	-
Supply voltage	12VDC
Power consumption	1.2W
Dimensions (HxWxD)	19x19x61,4 mm
Weight	55g (incl. stand)
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug



Your partner for eneo products:

