



## VK-1317S

Article-No.: 91926

1/3" Board Camera, B/W, 3.8mm,  
2.1Lux, 600TVL, 12VDC

### Mainfeatures

B&W CCD board camera  
Resolution of 600 horizontal lines  
Internal synchronization  
Interchangeable lens element

1/3" Sony Super HAD CCD  
Automatic shutter control (ESC)  
High sensitivity  
Supply voltage: 12VDC




### Specifications

System	black&white
Video standard	CCIR
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Active picture elements	440,000, 752(H) x 582(V)
Synchronization	internal
Gamma correction	0.45
Horizontal resolution	600 TVL
Sensitivity (at 50% video signal)	0,75 Lux
Sensitivity (at 50% video signal)	at F1.2 (measured)
Automatic electronic shutter (ESC)	1/50 ~ 1/100,000sec.
Low speed shutter	no
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no
Aperture Correction (APC)	yes
IR cut filter	no



## Specifications (continued)

Video outputs	composite (VBS)
Lens type	fixed focal length
Lens	F2,0 / 3.8mm with fixed focus
Focal length	3,8 mm
e-PTZ support	no
Digital zoom	no
Horizontal angle of view	65°
Iris control	no
MOD (Minimum object distance)	0,1 m
Illumination	no
Activity detection	no
Serial interfaces	no
Temperature range (operation)	-10°C ~ +50°C
Housing	without housing
Hidden cable management	no
Vandalism resistant	no
Protection rating	n/a
Alarm inputs	-
Alarm outputs	-
Supply voltage	12VDC
Power consumption	approx. 1.4W
Dimensions (HxWxD)	30x30x25mm
Weight	approx. 25g
Certificates	CE

## Optional Accessories

Image	Artikel-Nr. / Typ	Description
	H0225M	F2.5/2.5mm Board Camera Lens, 1/3" M12X0.5
	H0820M	F2.0/8mm Board Camera Lens, 1/3" M12X0.5
		F2.5/12mm Board camera lens, 1/3" M12x0.5

## Optional Accessories (continued)

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
	VT-PS12DC-9	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. open Ends

Your partner for eneo products:

