



VKCD-134/HR

Article-No.: 92207

1/3" Mini Dome, Fixed, Colour,
3.7mm, 550TVL, 12VDC

Mainfeatures

For wall and drop ceiling mounting
Built-in pinhole lens F2.0/3.7mm
Internal synchronization

Resolution of 550 horizontal lines
Automatic shutter control (ESC)
Easy installation


Specifications

System	colour
Video standard	PAL
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Horizontal resolution	550 TVL
Synchronization	internal
Gamma correction	0.45
Sensitivity (at 50% video signal)	0,5 Lux
Sensitivity (at 50% video signal)	at F1.2 (measured)
Low speed shutter	no
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no
IR cut filter	standard
Activity detection	no
Digital zoom	no
Lens type	fixed focal length
Focal length	3,7 mm

Specifications (continued)

Horizontal angle of view	68°
MOD (Minimum object distance)	0,1 m
Video outputs	composite (CVBS)
Video outputs	1Vp-p, CVBS, 75ohms
Alarm inputs	no
Alarm outputs	no
e-PTZ support	no
Rotation range	359°
Tilt range	approx. +/-60°
Illumination	no
External connections	Video (BNC), 12VDC (Cinch)
Serial interfaces	no
Housing	indoor
Housing material	aluminium
Colour (bubble)	-
Colour (housing)	anodized silver-coloured (C-0)
Heater	no
Mounting	flush mount, wall mount
Supply voltage	12VDC
Power consumption	0.72W
Temperature range (operation)	-10°C ~ +50°C
Protection rating	n/a
Vandalism resistant	no
Weight	120g
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug

Your partner for eneo products:

