

## GLS-2202H

Article-No.: 92527

Network 1-channel Video Server  
Board, H.264/MJPEG, 42x42mm,  
12VDC, PoE

### Mainfeatures

1 channel video server for LAN/WAN/Internet  
Image frame rate: up to 25 ips. (720x576 px.)  
Motion detection  
Supports various network environments  
E-Mail, FTP notification in case of an alarm  
Power supply: 12VDC and PoE

Simultaneous video streaming (H.264 & MJPEG)  
Audio and alarm input and outputs  
Integrated web server: 10Base-T/100Base-TX  
Viewer for monitoring, recording and configuration  
Export of AVI files or JPEG snapshots on SD card  
Set of connection cables as accessory



### Specifications

Series	eneo GL
System	PAL/NTSC
System requirements	Processor: Pentium IV, Core2 Duo; 2.8GHz; 512MB RAM; Microsoft Windows XP, Vista
Compression standard	MJPEG, MPEG-4
Ethernet interface	10Base-T, 100Base-TX
Network protocols	FTP, TCP/IP, HTTP, HTTPS, RTSP, RTP, RTCP, DHCP, UPnP, ARP, DNS, DDNS, SNTP, PPPoE, SMTP
Configuration	via web browser, built-in web server
Picture adjustments	Image quality: 5 levels
Data rate	up to 2.0MB/sec.
Playback	via CMS Viewer Software
Resolution	720x576 (4:3), 704x288 (4:3), 352x288 (4:3), 176x144 (4:3)
Resolution max.	720x576
Image transmission rate max.	25 B./Sek.
Frame rate	25 / 24 / 15 / 5 Fps.

## Specifications (continued)

Video inputs (amount)	1
Video inputs	1Vp-p, 75ohms
Video output	1 Vp-p, (C)VBS, 75 ohms
Audio support	yes
Audio input	1x line-in
Audio sampling rate	8kHz
Alarm inputs	yes
Alarm inputs	1
Alarm processing	alarm triggered by build-in motion detection, external alarm. Alarm notify to ANNP, e-mail, FTP, SD card, alarm out
System Integration	Comprehensive development SDK kit, including HTTP-API, Active-X control, customized Web page tool
Alarm output	1x Relais NO/NC contact
Alarm reset input	1x Relay contact input
e-PTZ support	yes
Activity detection	yes
Internal storage	SD card
Digital storage media	6 MB RAM (Pre alarm memory, MJPEG), SD card (external)
Access	8 users simultaneous support
Serial interfaces	RS-485
Firmware update	SD card / Web browser / FTP
Text display	date and time
Menu languages	German, English, French, Italian, Polish, Spanish, Finnish, Hungarian, Czech, Portugese
Password protection	yes
Password protection	multi level (administrators and users), IP filtering, HTTPS
Power over Ethernet	yes
Power over Ethernet	IEEE 802.3af
Supply voltage	12VDC, PoE
Power consumption	3.6W
Housing	-
Management Software Support	Zelaris, Netavis (limited), Aimetis - Symphony (limited), GL -Manager
ONVIF	no
Certificates	CE
Parts supplied	Connection cables: Ethernet (RJ-45), SD card slot, Video loop out/DC in, Video in/DC out, USB Mini Type B 2.0, Audio/Alarm In/Out/Reset, RS-485
19" Rack mountable	no
Dimensions (HxWxD)	42x42x25mm
Temperature range (operation)	0°C ~ +50°C

## Optional Accessories

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
	VT-PS12DCDT1	PSU 12VDC/1.0A, Regulated, Desktop Version, 1.8m Cables each w. open ends

Your partner for eneo products:

